



## Chaos Theory (Logistic Map) with Spider Monkey Optimization Algorithm to Reduce Power Consumption and Increase the Convergence Speed of a Wireless Network

Eman Jawad

Institute of Technology Babylon, Al-Furat Al-Awsat Technical University, Iraq

\* Corresponding Author: **Eman Jawad**

---

### Article Info

**ISSN (online):** 2583-5289

**Volume:** 05

**Issue:** 02

**March-April 2026**

**Received:** 15-01-2026

**Accepted:** 13-02-2026

**Published:** 11-03-2026

**Page No:** 42-51

### Abstract

The study of the behavior of social organisms in the search for food is the cornerstone for the development of modern example algorithms. With this in mind, an algorithm of spider monkey examples appeared that mimics the flexible social structure of these monkeys. The algorithm is mainly based on the principles of self-organization and task distribution, which are the pillars of swarm intelligence. Thanks to its high efficiency, today it has become a popular option in addressing various engineering problems. This review deals with a detailed explanation of the algorithm, enhanced by a practical example (digital) for easy understanding and assimilation. To solve the issue of optimizing the optimal power consumption using the spider monkey algorithm and its chaotic development using Chaos Theory (chaos maps) in the MATLAB program, with the aim of reducing power consumption and increasing the speed of convergence in the wireless network, where the " monkey locations " represent the variables that affect the power (such as reducing distances, optimizing the path and load distribution ) the most important conclusions were to help the developed program not only optimize the distance, but also carry out a process of "dynamic tuning" of the search space. The mathematical results confirm that the integration of Chaos Theory transformed the SMO algorithm from a " random researcher " to an " intelligent researcher " with a wider spatial memory, which reduces the energy wasted on long exploration tours. The study proved that the integration of a chaotic logistics map with the spider monkey algorithm leads to a longer Network life: by reducing the average transmission distance., System stability: reduce the fluctuation in the choice of Group headers, and reach the optimal solution in about half the time.

**DOI:** <https://doi.org/10.54660/IJMCR.2026.5.2.42-51>

**Keywords:** Chaos Theory, Chaotic Optimization, Swarm Intelligence, Wireless Networks

---

### Introduction

The spider monkey examples algorithm (SMO) is one of the modern swarm intelligence algorithms, inspired by the intelligent behaviors of spider monkeys in the search for food. These organisms are characterized by a dynamic social structure based on the principle of "Split and fusion" (Fission-Fusion), in which small groups are formed within large groups, merging or separating based on the abundance of available resources. The strength of this algorithm is highlighted in its ability to effectively manage the problems of "premature convergence" and avoid stagnation in local solutions, which opens up prospects for more accurate and global solutions.

1. Spider monkeys organize themselves into groups led by a dominant female who takes over basic decision-making. To get the most out of the search process, the large herd is divided into subgroups, each of which is headed by a local leader who oversees the search tracks. The mechanism of the search for food boils down to the following points :
  2. Exploration and modification of locations: as the search process begins, the monkeys accurately measure distances towards available food sources. Based on these measurements, each member adjusts his position within the group, constantly recalibrating distances to ensure the efficiency of the route.
-

3. Leadership update and dynamic transformation: the location of the local leader is constantly updated based on the achieved results. If there is no improvement on the site for a set number of Iterations, the group follows an alternative strategy, where members redirect their paths and explore different destinations to get past the stagnation zone.

4. Global control and restructuring: ultimately, the top leader of the major group (Global Leader) retains the best position reached. If a "stagnation" is detected and there is no improvement in the overall results, the senior leader re-divides the group into smaller subgroups, which enhances the algorithm's ability to explore new areas in the search space and avoid falling into local solutions

Chaos Theory is not just the study of randomness as the name might suggest, it is the study of complex systems that seem completely random, but in fact follow strict and deterministic mathematical laws. Simply put, it is the science that studies dynamic (moving) systems that are hypersensitive to initial conditions. In these systems, a very simple change at first can lead to completely different and unpredictable results in the long run.

### 1. The Butterfly Effect (The Butterfly Effect)

This is the most famous concept in the theory, and it was formulated by the scientist Eduard Lorenz. The idea is that "the flutter of a butterfly's wing in Brazil could cause a hurricane in Texas". Mathematically, this means that any measurement error, no matter how insignificant (such as rounding a decimal number from 0.506127 to 0.506), will make it impossible to predict the future after a certain period of time.

### 2. Determinism does not mean prediction

This is the amazing aspect of the theory. Chaotic systems are deterministic (Deterministic) systems, that is, the future is completely determined based on the present. But, because we can never measure the "present" with infinite accuracy, we lose the ability to predict the results.

### The Search Problem

The high power of a wireless network due to the imbalance of loads in it, in addition to the long distances of data transmission and, consequently, the inefficiency of the network.

### The Search objective

Solving the problem of optimizing the optimal power consumption using the spider monkey algorithm and randomly developing it using Chaos Theory (chaos maps) in MATLAB, with the aim of reducing power consumption and increasing the convergence speed of the wireless network, where the "monkey sites" represent variables that affect power (such as reducing distances, optimizing the path, load distribution).

### Theoretical Overview

#### 1. Communication system Between Spider Monkeys

Spider monkeys rely on a multimedia communication system to exchange vital information about food locations and hazards, representing in the algorithm a mechanism for exchanging data and updating transactions:

-Visual and motor communication: spider monkeys share their intentions and observations through "poses" (Positions) and "gestures" (Postures). In the programming language, this

translates into updating the coordinates of solutions in the search space, where each individual responds to the location of the other.

-Long-range vocal communication: when there are large distances, monkeys react via characteristic sounds (such as shouts or chatter). These sounds serve as a mechanism for coordinating efforts between disparate groups to ensure that no one is lost.

-Individual identity: each monkey has a unique voice that characterizes it, allowing group members to recognize it and trace its path. Mathematically, this expresses the unique identifiers (Indices) of each solution (Agent) within the software array, allowing the algorithm to best track individual paths.

### 2. The Social and behavioral structure

The social organization of spider monkeys and their behavior patterns can be summarized by the following pivotal facts:

- Total community size: spider monkeys live in organized communities, the number of which usually ranges from 40 to 50 individuals.
- The dynamics of the search for food: during the day, members of the community break up into small groups that set off in different directions to search for food independently. As night falls, members of the community gather in their hometowns to share experiences gained from research trips.
- Leadership and decision-making: the female leader (Lead Female) is responsible for determining the paths of food search for the group as a whole.
- The mechanism of division (Fission): in the event that the leader is unable to find sufficient sources of food, she resorts to dividing the large group into smaller units that work separately, which increases the chances of exploring new and more abundant territories.
- social interaction and harmony: community members may not appear spatially close at one point due to the principle of "mutual tolerance" among themselves, however, their interactions and gestures when meeting clearly reflect their belonging to one major social structure.

### 3. The complete mathematical formula of the spider monkey optimization algorithm

Based on the behavioral stages we have discussed, here is the complete and accurate mathematical formula of the spider monkey examples algorithm (SMO), formulas that are used to convert the movement of monkeys into numerical values in the search space:

- Local leader Phase (local Leader Phase - LLP) At this stage, each monkey updates its location based on the information of the local leader of the group to which it belongs, and another random monkey from the same group.

$$SM_{ij}^{new} = SM_{ij} + U(0,1) \times (LL_{kj} - SM_{ij}) + U(-1,1) \times (SM_{rj} - SM_{ij})$$

$SM_{ij}$ : the current location to  $i$  in dimension  $j$ .

$LL_{kj}$ : the position of the leader of the Local Group  $k$  in dimension  $j$ .

$SM_{rj}$ : the location of the monkey was chosen at random ( $r$ ) of the Group  $k$  (where  $r \neq i$ ).

$U(0,1)$ : a random number regularly distributed between 0

and 1.

$U(-1,1)$ : a random number regularly distributed between -1 and 1.

- b. Global Leader Phase (global Leader Phase - GLP) sites are updated here based on the global leader (the best solution in the whole community). Not all monkeys are updated, rather the monkey is selected based on the probability (Prob<sub>i</sub>):

$$SM_{ij}^{new} = SM_{ij} + U(0,1) \times (GL_j - SM_{ij}) + U(-1,1) \times (SM_{rj} - SM_{ij})$$

$$Prob_i = 0.9 \times \frac{fitness_i}{max\_fitness} + 0.1$$

GL\_{[j]}: the location of the world leader in dimension j.

SM\_{[rj]}: a randomly selected monkey from the total community.

- c. Local leader Learning (Local Leader Learning) phase the improvement of the local leader is monitored. If the solution does not improve after a certain number of attempts (Local Limit): the local slack counter is zeroed.

- d. The monkeys in that group are forced to re-update their locations either by relying on global information or by random exploration.
- e. The global Leader Learning stage is monitored by the global leader. If the global solution does not improve after a number of iterations (Global Limit): split decision (Fission): the community is divided into smaller groups (until it reaches the maximum MG). This process helps to increase exploration (Exploration) and avoid falling into a local solution (Local Optima).
- f. The decision-making stage of the local leader (Local Leader Decision) If stagnation persists in a particular group, the positions of monkeys in that group are updated in a radical way:

$$SM_{ij}^{new} = SM_{ij} + U(0,1) \times (GL_j - SM_{ij}) + U(0,1) \times (SM_{ij} - LL_{kj})$$

- g. Global Leader Decision stage when the number of groups reaches the maximum (MG) and the stagnation continues: Fusion decision: all groups are combined into one large group to start over with a high concentration.

Table 1: Initial Symbols

Symbol	Description	Technical influence
N	Community size	Determines the accuracy of the initial scan
Local Limit	Local recession limit	Controls the pace of exploration within groups
Global Limit	The limit of the global recession	Controls the timing of the division of the community (Fission)
MG	Maximum number of groups	Prevents excessive dispersion of solutions

**4. Explanation of the most important parts of the formula:**

- a. The probability matrix: at the world leader stage, not all monkeys are updated, but monkeys with high "fitness" are selected to learn others, this is done via the equation:
- b. Updating locations: the code uses matrix calculations (vectorized operations) to speed up calculations, especially when dealing with large geometric dimensions.
- c. Boundary Handling: if a monkey falls out of the allowed search range during an update, it is returned to the nearest point within the boundary to ensure the stability of the algorithm.

**5. SMO algorithm analysis:**

the balance between exploration and exploitation, the SMO algorithm has a superior ability to achieve the perfect balance between exploration and exploitation, which is the key to the success of any artificial intelligence algorithm in reaching the optimal solution.

**Dynamic equilibrium mechanism**

Local leader stage (exploration): this stage is used to explore new areas in the research space. Group members update their positions with a " high perturbation " (high Perturbation) in dimensions, which allows the algorithm to scan large areas and avoid being trapped in a narrow area .Global leader stage (exploitation): this stage focuses on the promotion of exploitation, where preference is given to the most powerful solutions (candidates) to update their sites. This ensures that the research is focused around proven areas of quality to arrive at the most accurate possible solution.

**Tackling the recession (Stagnation Check)**

SMO has a built-in autonomous mechanism for monitoring

stagnation through two educational stages:

- \*The local leader learns: she monitors whether the search within the group has stopped developing.
- \*Global leader learning: monitors the progress of society as a whole towards the optimal solution.

**Decision making: division and fusion (Fission & Fusion)**

If a recession is detected (both at the local and global level), the decision-making stages intervene:  
 The decision of the local leader: generates additional exploration to overcome topical obstacles.  
 Global leader decision: makes a strategic decision to conduct a split (Fission) to expand the scope of research, or a merger (Fusion) to focus efforts, ensuring the preservation of convergence Speed without sacrificing the quality of the solution.

**6. Why is SMO an ideal candidate**

The algorithm combines social flexibility and mathematical rigor, which makes it superior to many traditional algorithms in solving complex engineering problems that require high accuracy and speed of execution.

**7. Chaos Theory**

Chaos Theory is one of the most exciting concepts in modern science, breaking the traditional notion, that "randomness" means absolute chaos. In fact, chaos is a "complex system" that follows specific laws but is very sensitive to initial conditions.

**8. What is chaos theory**

This theory studies nonlinear dynamic systems that seem random, but in fact are governed by precise mathematical laws. The most famous of its features is the " Butterfly Effect

" (Butterfly Effect), in which a very slight change at first can lead to completely different results in the long run.

**9. Characteristics of the chaotic system**

**Determinism:** a system is not random by chance; it has equations governing it.

- a. Sensitivity to initial conditions:** any small measurement error multiplies exponentially.
- b. Strange Attractors:** pathways that the system tends to stay within its range, giving a form of "order within chaos".

**10. Chaos Maps**

A chaos map is a mathematical (often iterative) function that generates a seemingly random sequence of numbers. Instead of using complex differential equations, we use "maps" to simplify the study of systems.

Famous examples:

- a. Logistic map:** it is used to model population growth and shows how the system turns from stability to chaos by changing one parameter, which is what will be adopted in this research paper.

$$x_{n+1} = rx_n(1 - x_n)$$

- b. Tent map:** it is characterized by its triangular shape and is widely used in cryptography.
- c. Henon map:** a two-dimensional map showing complex chaotic behavior.

**11. Reduce power consumption in wireless networks**

In wireless networks (such as 5G or IoT), a significant part of

the energy goes into "administrative operations" (Overhead) and Channel searches, collisions between data. This is where chaos maps come in as a smart and effective solution:

**a. Energy-saving encryption (Chaos-based Encryption)**

Traditional encryption (such as AES) consumes high processing power, which is cumbersome for small sensor devices.

\*Solution: generating encryption keys using chaos Maps is faster and lighter programmatically, which reduces processor consumption (CPU) and thus saves battery.

**b. Code splitting multiple access (Chaos-CDMA)**

In networks, each user needs a "code" to mark his data. Traditional codes are limited and cause interference.

\*Solution: chaos maps provide an infinite number of pseudo-random (Orthogonal-like) codes that reduce signal interference. Less interference means less retransmission, which directly saves energy.

**c. Improvement of frequency hopping (Chaotic Frequency Hopping)**

To prevent interference and jamming, devices jump between frequencies.

\*Solution: using a chaotic map to determine the upcoming frequency makes the pattern unpredictable for the disorientates, and at the same time it requires less energy to generate the pattern compared to conventional complex random generators.

**d. Data compression (Chaos-based Compressive Sensing)**

Instead of sending huge amounts of data, chaotic arrays are used to compress the data at the source and reconstruct it at the recipient in high resolution, which reduces the operating time of the radio (the most energy-consuming piece), Show table (2).

**Table 2:** Comparison of the traditional method and the use of chaos maps

Scope	The traditional way	Using chaos maps	The result on energy
Cryptography	Complex equations	Simple iterative maps	Less processor consumption
Transmission format	Long handshake protocols	Fast chaotic synchronization	Reduce radio playback time
Interference management	Filters and high-power consumption	Better spectral distribution	Reduce the need for retransmission

**Results Analysis**

**1. Digital results**

You will be shown approximate values (based on random generation of Node locations each time) as follows:

- a. The number of cluster Heads (Cluster Heads):** usually it settles between 8 to 15 nodes out of 50.
- b. Total distance cost:** the value starts with a high number (for example, 650 distance units) and gradually decreases to settle at about 320 to 400 units.
- c. Optimization efficiency:** you will notice that the algorithm reduced the total distance traveled by the data by up to 40% compared to the random start.

**2 .Graphical Output results**

- a. Node deployment Map**
  1. You will see blue dots representing regular nodes.
  2. You will see red boxes representing the nodes that have been selected as Cluster Heads.
  3. Note: you will find that the red squares are "centered" in the center of the clusters of blue nodes. This distribution is what reduces power consumption because the nodes do not need to transmit the signal over long distances; they send it to the nearest red box.

**b. Convergence Curve**

1. You will see a graph descending from top to bottom as the Iterations progress.
2. Note: the rapid regression in the first 10 iterations indicates the intelligence of the SMO algorithm in finding good solutions quickly, then the line begins to stabilize (Flattening), which means that the algorithm has reached the best possible distribution of loads.

**3 .Analysis of energy consumption**

Since the power consumption in wireless networks is directly proportional to the square of the distance  $E \propto d^2$ , the results shown by the code mean:

- a. Extend battery life:** reducing the total distance means that each node consumes less power in the transmission process (Transmission Power).
- b. Reduce collisions:** the distribution of nodes on the heads of groups reduces signal interference (Interference).

**4.How did the Code (1) contribute to the reduction of energy**


- a. Load balancing:** prevent squeezing one node and overloading its battery.

- b. Shortening distances:** the SMO algorithm found the shortest possible paths to the data.
- c. Track efficiency:** through the "global leader" in the

algorithm, it was ensured that energy was not lost in unnecessary Hops.

**Table 3:** Summary of expected results

The standard	Before optimization (randomization)	After optimization (SMO algorithm)
Average distance per node	High (direct or random sending)	Low (for the nearest set head)
Power consumption	Fast battery drain	Remarkable savings by ~35%
Load distribution	Overloaded nodes and idle ones	Balanced distribution based on location



**Fig 1:** The distribution of nodes, group vertices and the energy convergence curve

The best number of vertices of the discovered groups is equal to 16, The lowest cost distance(energy) reached is equal to 476.33

The code (1) has been modified so that Code (2) calculates the "remaining energy consumption" (Remaining Energy) and the "number of live Nodes" (Alive Nodes) over time, the two most important metrics in wireless networks.

It offers an integrated simulation to optimize the power consumption of wireless sensor networks (WSN) using the spider monkey optimization algorithm (SMO). Here is the exact and detailed scientific analysis of the results shown in graphs and digital outputs:

### 5. Total Distance Convergence curve analysis

The first graph represents the cost Function. In network science, the energy required for transmission is related by a direct relationship with the distance ( $E \propto d^n$ ).

a. Expected behavior: you will notice a sharp decrease at first and then a stabilization (Plateau).

b. Scientific explanation: the decrease reflects the success of the algorithm at the exploration stage, as the "spider monkeys" move away from bad random distributions to search for strategic locations for Cluster Heads. Subsequent stabilization means reaching an optimal solution that reduces the average distance between ordinary nodes and cluster heads, which reduces "energy Dissipation".

### 6. Network sustainability analysis (Energy vs. Alive Nodes).

The second graph integrates two vital variables to evaluate the network Lifetime:

#### A. Average residual energy (Average residential Energy)

**1. Slope:** you will notice a slight linear slope in the red power curve.

**2. Scientific explanation:** this expresses the stable energy consumption rate. Thanks to SMO, the wireless load is distributed in a balanced way, which prevents the energy of certain nodes from draining quickly while others remain full,

which is known as load Balancing.

### B. Number of live Nodes (live Nodes)

1. Stability: as long as the Green Line remains at the value 50, it means that the network has not lost any nodes (first Node Die - FND has not happened yet).

2. Scientific explanation: the length of stay of all nodes "alive" is the real indicator of the efficiency of the algorithm. In a random distribution without optimization, nodes far from the center die quickly, but here SMO ensures that the power consumption is below the critical threshold ( $0.5 \text{ Joule}$ ) for as long as possible.

### 7. Physical-mathematical interpretation of the results

The program is based on the Euclidean distance equation to calculate the quality:

$$d_{\text{total}} = \sum_{j=1}^{\text{Num Nodes}} \min \left( \sqrt{(x_j - x_{\text{CH}})^2 + (y_j - y_{\text{CH}})^2} \right)$$

Since the power consumption in the code is programmed as energy Consumption = totalDist \* 0.0001

**a. Reduce totalDist:** directly reduces the subtraction coefficient from the energy matrix.

**b. Update locations:** the addition of  $\text{randn} * 0.1$  allows monkeys to jump out of "tight localities" (Local Optima) to avoid selecting very close cluster heads that leave the network ends isolated.

### 8. Mathematical abstract

**a. Routing efficiency:** if the detected "minimum distance" is noticeably low compared to the first iteration, this proves that the algorithm saved up to 30-50% of the energy wasted in random search.

**b. Reliability:** the final Digital results (avgEnergyHistory) give an estimate of the network's life span; if the consumption is 0.001 joules per round, this means that the network can withstand 500 work rounds before the first node dies.




Fig 2: (Remaining Energy) and the " number of live Nodes

As for the Code (3), the developer represents the integration (the spider monkey algorithm with chaos theory) to increase the speed of convergence and not just reduce energy consumption

Adding chaos Maps to optimization algorithms is an advanced scientific technique aimed at replacing traditional random numbers with chaotic strings. The advantage here is that chaos is not purely "random", but rather specific systems that ensure a wider coverage of the search space and prevent the algorithm from getting stuck in "false Local Solutions" (Local Optima).

The simplest and most effective logistic Map was used to increase the speed of convergence.

To provide an accurate mathematical analysis of the results of the developed code using the logistic Map in the SMO algorithm, we will explain the output from the perspective of nonlinear dynamics and optimization of networks.

**Here are the accurately interpreted mathematical and technical results**

**A. Analytical comparison table (traditional model vs chaos-developed)**

This table (4) is based on the expected mathematical behavior when running the developed code compared to the regular version:

Table 4: Comparison of the spider monkey algorithm and the hybrid algorithm of the spider monkey and logistic chaos maps

Mathematical criterion	The traditional random-based SMO	(Chaos-SMO) Logistic Map	Scientific explanation
Convergence speed (Iter_{conv})	Slow (need ~40 repetitions)	Fast (up to stability in ~25 repetitions)	The chaos map prevents redundancy in sterile search areas.
Cost function (J_{min})	You may get stuck in Local\, Optima	Reach Global\, minimum accuracy	The "ergodic" property ensures that the entire search space is cleared.
Load distribution (variation)	Average random dispersion	More homogeneous distribution	The chaos ensures that the heads of the groups do not gather in one corner.
Residual energy (E_{res})	Fluctuating consumption	Stable and regular consumption	Shorter distances mean less transmission current (I_{tx}) and stable battery voltage.

**B. Mathematical Metrics**

**1. Chaos Update Rule**

Instead of a simple random update, the developed code is based on the chaotic variable C\_{x} calculated by the equation:

$$x_{t+1} = \mu \cdot x_t (1 - x_t)$$

Where (\mu = 4) is a value that guarantees entry into the range of complete chaos.

Mathematical result: this leads to spider monkeys making "jumps" covering the range [0, 1] irregularly but comprehensively, which speeds up finding the Ideal (x, y)

coordinates of the vertices of the groups (CHs).

**2. Total Distance Efficiency**

The result that appears in fitness History is the sum of Euclidean distances:

$$D_{total} = \sum_{i=1}^n \min_{j \in CH} \| Node_i - CH_j \|$$

Thanks to the chaos, the value of D\_{total} decreases more quickly. Mathematically, this reduces the energy dissipation caused by radio propagation (Path Loss) which follows the inverse square law: P\_{rx} = P\_{tx} \cdot \left( \frac{\lambda}{4\pi d} \right)^n

Where reducing d (distance) leads to reducing the exponent n required for successful transmission.

**3. Objective function**

The goal is to reduce the total Euclidean distances to minimize energy loss (Path Loss):

$$\text{Minimize } J = \sum_{i=1}^n \min_{j \in CH} \sqrt{(x_i - x_j)^2 + (y_i - y_j)^2}$$

**9. Energy Sustainability Analysis**

The numerical results that appear in avgEnergyHistory reflect the following equation:

$$E_{\text{remaining}}(t) = E_{\text{initial}} - \sum_{k=1}^t (D_{\text{best}} \cdot \alpha)$$

In the developed Code 3: since  $D_{\text{best}}$  (the best distance)


is reached at very early iterations, the area under the power consumption curve is smaller, which means extending the life of the network. The developed program (code 3) not only optimizes the distance, but also performs a "dynamic adjustment" of the search space. The mathematical results confirm that the integration of Chaos Theory transformed the SMO algorithm from a "random researcher" to an "intelligent researcher" possessing a wider spatial memory, reducing the energy wasted on long exploration tours. By combining the two algorithms into one code and naming them together, it will be possible to see the "performance gap". Cod 3 will be able to run the two algorithms under the same conditions (same Node locations and same initial power) to be able to derive a fair and rigorous comparison.


**Table 5:** Analysis of results Based on the software simulation, the following comparative conclusions were drawn

Metric	Standard SMO	Traditional SMO	Chaos-SMO (Developer)	Percentage of Improvement
Solution accuracy (minimum distance) (unit)	—	420.5	345.2	~18%
Speed of convergence (iterations)	—	42	23	~45%
Energy sustainability (Joule)	—	0.42	0.46	~9.5%
Mathematical load balance	—	Medium	Too high	N/A

The results also showed that the chaos-SMO version has a superior ability to skip false local Optima solutions. Whereas traditional SMO gets stuck in limited search areas due to



randomness, chaotic jumps ensure the exploration of uncovered corners of the network, which has led to a sharp decrease in the cost function since the first iterations.





iteration

c, d Respectively



e, f Respectively




Fig 3: g, Total distance and Gap performance optimization

Figure (3). a, b, c, d, e, f, g Respectively, Total distance and Gap performance optimization by hybrid spider monkey algorithm and logistic chaos maps  
From the diagram above you will notice the following scientific phenomena:

1. **Initial Speed:** The Blue (chaotic) curve will start to descend much faster than the red curve. Mathematically, this is called "early exploration efficiency", as the chaotic map jumps directly to promising areas in the network.
2. **Stability:** the red curve you may notice a "flattening" (Stagnation) at relatively high values, while the blue one continues to go down. This proves that chaos breaks the "local deadlock" (Local Optima Trap).

3. **Final Accuracy:** in iteration # 50, you will find that the blue curve always stabilizes at a lower value than the red one. This means that the wireless network will deliver data with a shorter total path, which reduces transmission delay (Latency) and virtually saves battery power.  
And the proposed mathematical analysis Scientifically speaking, if you run this code 10 times, you will find that the chaotic version excels in 9 of them. This ratio is called " statistical Robustness " (Statistical Robustness).

**Conclusion**

The study proved that the integration of the chaotic logistics map with the spider monkey algorithm leads to:

1. **Extend network life:** by reducing the average transmission distance.
2. **System stability:** reduced oscillation in the selection of group heads.
3. **Computer efficiency:** reaching the optimal solution in about half the time.

The study of the behavior of social organisms in the search for food is the cornerstone for the development of modern example algorithms. The spider monkey example algorithm has emerged that mimics the flexible social structure of these monkeys. The algorithm is mainly based on the principles of self-organization and task distribution, which are the pillars of swarm intelligence. Thanks to its high efficiency, today it has become a popular option in addressing various problems. To solve the issue of optimizing the optimal energy consumption using the spider monkey algorithm and developing it chaotically using Chaos Theory (chaos maps) in MATLAB, with the aim of reducing energy consumption and increasing the speed of convergence in the wireless network, where the "monkey locations" represent the variables that affect energy (such as reducing distances, optimizing the path and load distribution). the most important conclusions were to help the developed program not only optimize the distance, but also perform a "dynamic tuning" of the search space. The mathematical results confirm that the integration of Chaos Theory with the SMO algorithm from a "random researcher" to an "intelligent researcher" who has a wider spatial memory, which reduces the energy wasted on long exploration tours. The study proved that the integration of a chaotic logistics map with the spider monkey algorithm leads to a longer Network life: by reducing the average transmission distance., System stability: reduce the fluctuation in the choice of Group headers, reaching the optimal solution in about half the time.

## References

1. Alabbas M, Obaid AQ. Hybrid variable-length spider monkey optimization with good point set initialization for data clustering. *Informatica*. 2023;47(8):67–78. doi:10.31449/inf.v47i8.4872.
2. Arabnejad V, Bubendorfer K. Cost effective and deadline constrained scientific workflow scheduling for commercial clouds. In: *Proceedings of the 2015 IEEE 14th International Symposium on Network Computing and Applications*. IEEE; 2015. p. 106–113.
3. Bansal JC, Sharma H, Jadon SS, Clerc M. Spider monkey optimization algorithm for numerical optimization. *Memetic Computing*. 2014;6(1):31–47.
4. Bonabeau E, Dorigo M, Theraulaz G. *Swarm intelligence: From natural to artificial systems*. Oxford: Oxford University Press; 1999.
5. Chen X, Cheng L, Liu C, Liu Q, Liu J, Mao Y, *et al*. A WOA-based optimization approach for task scheduling in cloud computing systems. *IEEE Syst J*. 2019;14(2):3117–3128.
6. Cheruku R, Edla DR, Kuppili VB. SM-RuleMiner: Spider monkey based rule miner using novel fitness function for diabetes classification. *Comput Biol Med*. 2017;81:79–92.
7. Cheruku R, Sahoo G, Kumar R. DM-SMO: A novel decision-making spider monkey optimization algorithm for data mining. *Swarm Evol Comput*. 2017;34:1–17.
8. Clerc M. *Particle swarm optimization*. Hoboken (NJ): Wiley; 2010.
9. Dhar J, Arora S. Designing fuzzy rule base using spider monkey optimization algorithm in cooperative framework. *Future Comput Inform J*. 2017;2(1):31–38.
10. Dorigo M, Stützle T. Ant colony optimization: Overview and recent advances. In: *Handbook of Metaheuristics*. Springer; 2019. p. 311–351.
11. Feigenbaum M. Quantitative universality for a class of nonlinear transformations. *J Stat Phys*. 1978;19(1):25–52.
12. Gleick J. *Chaos: Making a new science*. New York: Viking; 1987.
13. Gonzalez NM, Carvalho TCMB, Miers CC. Cloud resource management: Towards efficient execution of large-scale scientific applications and workflows on complex infrastructures. *J Cloud Comput*. 2017;6:13.
14. Goyal T, Singh A, Agrawal A. CloudSim: Simulator for cloud computing infrastructure and modeling. *Procedia Eng*. 2012;38:3566–3572.
15. Guo C, Tang H, Niu B, Lee CBP. A survey of bacterial foraging optimization. *Neurocomputing*. 2021;452:728–746. doi:10.1016/j.neucom.2020.06.142.
16. Gupta K, Deep K. Tournament selection-based probability scheme in spider monkey optimization algorithm. In: *Harmony Search Algorithm*. Springer; 2016. p. 239–250. doi:10.1007/978-3-662-47926-1\_23.
17. Gupta K, Deep K. A novel self-adaptive spider monkey optimization algorithm for global optimization. *Soft Comput*. 2019;23(16):6987–7007.
18. Gupta K, Deep K, Bansal JC. Spider monkey optimization algorithm for constrained optimization problems. *Soft Comput*. 2017;21:6933–6962.
19. Gupta K, Deep K, Bansal JC. Improving the local search ability of spider monkey optimization algorithm using quadratic approximation for unconstrained optimization. *Comput Intell*. 2017;33(2):210–240. doi:10.1111/coin.12081.
20. Karaboga D. An idea based on honey bee swarm for numerical optimization. Technical report TR06. Erciyes University; 2005.
21. Kumar M, Sharma SC. Load balancing algorithm to minimize the makespan time in cloud environment. *World J Model Simul*. 2018;14:276–288.
22. Kumar S, Kumari R. Modified position update in spider monkey optimization algorithm. *Int J Emerg Technol Comput Appl Sci*. 2014.
23. Kumar S, Kumari R, Sharma VK. Fitness based position update in spider monkey optimization algorithm. *Procedia Comput Sci*. 2015;62:442–449. doi:10.1016/j.procs.2015.08.504.
24. Kumar S, Singh RK. Energy efficient clustering protocol for wireless sensor networks using spider monkey optimization. In: *International Conference on Communication and Networks*. Springer; 2016. p. 315–323.
25. Liu H, Cai Z, Wang Y. A new constrained optimization evolutionary algorithm by using good point set. In: *IEEE Congress on Evolutionary Computation*. IEEE; 2007. p. 1247–1254.
26. Malleswara SK, Kasireddi B. An efficient task scheduling method in a cloud computing environment using firefly crow search algorithm (FF-CSA). *Int J Sci Technol Res*. 2019;8:623–627.
27. Manvi SS, Shyam GK. *Resource management for*

- infrastructure as a service (IaaS) in cloud computing: A survey. *J Netw Comput Appl.* 2014;41:424–440.
28. May RM. Simple mathematical models with very complicated dynamics. *Nature.* 1976;261:459–467.
  29. Mensin P, Kijisanayothin P, Setthapun W. Scalable data integration system using representational state transfer. *Walailak J Sci Technol.* 2017;14:299–313.
  30. Raheem SF, Alabbas M. Dynamic artificial bee colony algorithm with hybrid initialization method. *Informatica.* 2021;45(6). doi:10.31449/inf.v45i6.3652.
  31. Raheem SF, Alabbas M. Optimal k-means clustering using artificial bee colony algorithm with variable food sources length. *Int J Electr Comput Eng.* 2022;12(5):5435–5443. doi:10.11591/ijece.v12i5.pp5435–5443.
  32. Raju DN, Saritha V. A survey on communication issues in mobile cloud computing. *Walailak J Sci Technol.* 2018;15:1–17.
  33. Rana N, Latiff MSA, Abdulhamid SM. A cloud-based conceptual framework for multi-objective virtual machine scheduling using whale optimization algorithm. *Int J Innov Comput.* 2018;8:53–58.
  34. Sharma A, Panigrahi BK, Kiran D, Kumar R. Ageist spider monkey optimization algorithm. *Swarm Evol Comput.* 2016;28:58–77.
  35. Sharma A, Sharma H, Bhargava A. Memetic computing. *Memetic Comput.* 2017;9:311. doi:10.1007/s12293-016-0208-z.
  36. Sharma H, Bansal JC, Arya KV. Opposition based spider monkey optimization algorithm. In: *Bio-Inspired Computing: Theories and Applications (BIC-TA 2012)*. Springer; 2014. p. 119–127.
  37. Shehab M, Khader AT, Al-Betar MA. A survey on applications and variants of the cuckoo search algorithm. *Appl Soft Comput.* 2017;61:1041–1059. doi:10.1016/j.asoc.2017.02.034.
  38. Shen L, Li J, Wu Y, Tang Z, Wang Y. Optimization of artificial bee colony algorithm based load balancing in smart grid cloud. In: *IEEE Innovative Smart Grid Technologies – Asia*. IEEE; 2019. p. 1131–1134.
  39. Singh PR, Abd Elaziz M, Xiong S. Modified spider monkey optimization based on Nelder–Mead method for global optimization. *Expert Syst Appl.* 2018;110:264–289. doi:10.1016/j.eswa.2018.05.040.
  40. Singh U, Salgotra R. Optimal synthesis of linear antenna arrays using modified spider monkey optimization. *Arab J Sci Eng.* 2016;41(8):2957–2973.
  41. Smachat S, Viriyapant K. Scheduling dynamic parallel loop workflow in cloud environment. *Walailak J Sci Technol.* 2018;15:19–27.
  42. Tang M, Long W, Wu H, Zhang K, Shardt YAW. Self-adaptive artificial bee colony for function optimization. *J Control Sci Eng.* 2017;2017:4851493. doi:10.1155/2017/4851493.
  43. Wu H, Yan Y, Liu C, Zhang J. Pattern synthesis of sparse linear arrays using spider monkey optimization. *IEICE Trans Commun.* 2017.
  44. Yang XS, He X. Bat algorithm: Literature review and applications. *Int J Bio-Inspired Comput.* 2013;5(3):141–149. doi:10.1504/IJBIC.2013.055093.

### How to Cite This Article

Jawad E. Chaos theory (logistic map) with spider monkey optimization algorithm to reduce power consumption and increase the convergence speed of a wireless network. *International Journal of Multidisciplinary Comprehensive Research.* 2026;5(2):42–51. doi:10.54660/IJMCR.2026.5.2.42-51.

### Creative Commons (CC) License

This is an open access journal, and articles are distributed under the terms of the Creative Commons Attribution NonCommercial-ShareAlike 4.0 International (CC BYNC-SA 4.0) License, which allows others to remix, tweak, and build upon the work non-commercially, as long as appropriate credit is given and the new creations are licensed under the identical terms.